


02/28/00

Please type a plus (+) inside this box - 

02-29-00

A

PTO/SB/29 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>		<b>Attorney Docket No.</b>	8236-043-999	<b>Total Pages</b>	27
		<b>First Named Inventor or Application Identifier</b>			
		Morris and Schwartz			
		<b>Express Mail Label No.</b>	EL 236 252 956 US		

<b>APPLICATION ELEMENTS</b> <i>See MPEP chapter 600 concerning utility patent application contents.</i>  1. <input checked="" type="checkbox"/> Fee Transmittal Form <i>Submit an original, and a duplicate for fee processing</i>  2. <input checked="" type="checkbox"/> Specification <span style="float: right;">[Total Pages 13]</span> <i>(preferred arrangement set forth below)</i> -Descriptive title of the Invention -Cross Reference to Related Applications -Statement Regarding Fed sponsored R&D -Reference to Microfiche Appendix -Background of the Invention -Brief Summary of the Invention -Brief Description of the Drawings <i>(if filed)</i> -Detailed Description of the Invention <i>(including drawings, if filed)</i> -Claim(s) -Abstract of the Disclosure  3. <input checked="" type="checkbox"/> Drawing(s) <i>(35 USC 113)</i> <span style="float: right;">[Total Sheets 7]</span>  4. <input checked="" type="checkbox"/> Oath or Declaration <span style="float: right;">[Total Sheets 2]</span>  a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) <i>(for continuation/divisional with Box 17 completed)</i> <i>[Note Box 5 below]</i> i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33 (b).  <input type="checkbox"/> Incorporation By Reference <i>(useable if Box 4b is checked)</i> The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	<b>ADDRESS TO:</b> Assistant Commissioner for Patents Box Patent Application Washington, DC 20231  6. <input type="checkbox"/> Microfiche Computer Program <i>(Appendix)</i>  7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission <i>(if applicable, all necessary)</i> a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy <i>(identical to computer copy)</i> c. <input type="checkbox"/> Statement verifying identity of above copies
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>ACCOMPANYING APPLICATION PARTS</b>	
8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input type="checkbox"/> Power of Attorney <i>(when there is an assignee)</i> 10. <input type="checkbox"/> English Translation Document <i>(if applicable)</i> 11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) <i>(Should be specifically itemized)</i> 14. <input type="checkbox"/> Small Entity Statement filed in prior application, Status still proper and desired 15. <input type="checkbox"/> Certified Copy of Priority Document(s) <i>(if foreign priority is claimed)</i> 16. <input type="checkbox"/> Other:	

<b>17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:</b> <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No: filed .		
<b>18. CORRESPONDENCE ADDRESS</b>		
<input checked="" type="checkbox"/> Customer Number or Bar Code Label	20583 <small>(Insert Customer No. or Attach bar code label here)</small>	or <input type="checkbox"/> Correspondence address below
<b>NAME</b>		
<b>ADDRESS</b>		
<b>CITY</b>		<b>STATE</b>
<b>COUNTRY</b>		<b>ZIP CODE</b>
<b>TELEPHONE</b>		<b>FAX</b>

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

**FORCE SENSOR ASSEMBLY**  
**FOR AN INFUSION PUMP**

**TECHNICAL FIELD**

The present invention relates generally to a force sensor assembly for use in infusion pumps. More particularly, the present invention relates to an assembly that reduces a load cell's sensitivity to the placement of an intravenous tube on the force  
5 sensor assembly in an infusion pump.

**BACKGROUND OF THE INVENTION**

Various devices have been developed to administer intravenous (IV) fluids to patients. One such device, a peristaltic infusion pump, operates a series of fingers or  
10 rollers which deform and occlude a resiliently deformable IV drip tube at multiple points sequentially along the tube's length. These occlusions form a wave like motion which forces the IV fluid under positive pressure along the tube. After each successive occlusion, the tube resiliently rebounds to its original diameter. The repetitive deformation of the tube may, however, ultimately weaken the resilience of  
15 the tube material. After prolonged use, a tube may not fully rebound to its former shape, thereby partly or fully occluding the tube at a point along its path. In addition, IV drip sets often contain clamps, which can be inadvertently be left closed, thus partly or fully occluding the tube.

In order to effectively control IV fluid delivery, it is essential that the infusion  
20 system constantly determine whether fluid is in fact being delivered to the patient.

Interruptions of the fluid flow may occur for a number of reasons, such as for example, occlusion of the tube or a blocked catheter. If the pump mechanism does not stop when the tube is occluded, either the pump will stall, the pump will continue to run with no fluid delivered, or the fluid pressure in the tube will increase until the  
5 obstruction catastrophically clears, possibly injuring the patient.

Accordingly, many infusion pump systems include a force or pressure sensor to determine whether there is an increase or loss of pressure within the tube. The sensor determines whether the fluid flow in the tube has been interrupted, and the pumping mechanism may be stopped and/or medical personnel notified. Because of  
10 the potentially harmful consequences of such interruptions, it is important that these sensors be as accurate and reliable as possible. Also, due to an infusion pump's portability and arduous operating conditions, it is desirable for these sensors to be small and rugged.

Force or pressure sensors used in infusion pumps typically contain a plunger  
15 that is either constrained in some way, such as with a pin in a hole, or of a free floating type. A constrained plunger type force sensor assembly could be comprised of an actuation plunger connected to a pin positioned and guided within a hole in a sensor housing. A transducer or load cell is positioned along the central axis of the plunger, remote from an IV drip tube. When the IV drip tube is positioned directly over the  
20 central axis of the plunger, a force created by the internal pressure of the IV drip tube is applied via the plunger and pin to the load cell, which measures the applied force. In this scenario, the measured force would be comparatively accurate as there is typically only a small loss of transferred force due to friction. However, when the IV drip tube is positioned off-center to the plunger's central axis, the plunger tends to  
25 rotate causing side loading on the plunger pin by the sensor housing which may bind the plunger pin in the hole. This side loading creates a friction force between the plunger pin and the sensor housing which results in a loss of force being applied to the load cell. This friction force ultimately leads to inaccurate and unreliable force measurement results. The above scenario may occur for example where an IV tube is  
30 misplaced on the force sensor assembly or where the tube drifts along the plunger surface during use.



## BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the nature and objects of the invention, reference should be made to the following detailed description taken in conjunction with the accompanying drawings, in which:

5           FIG. 1 is a cross sectional diagrammatic view of an IV tube enclosed within an infusion pump;

          FIG. 2 is an exploded isometric view of an embodiment of the present invention;

          FIG. 3 is an isometric view of the present invention with an IV tube in a first  
10   orientation;

          FIG. 4 is a diagrammatic side view of the sensor assembly of FIG. 3;

          FIG. 5 is an isometric view of an alternative embodiment of the invention;

          FIG. 6 is an isometric view of yet another alternative embodiment of the invention;

15           FIG. 7 is an isometric view of an embodiment of the present invention with an IV tube in a second orientation;

          FIG. 8 is a diagrammatic side view of the sensor assembly of FIG. 7;

          FIG. 9 is a diagrammatic side view similar to that of FIG. 8;

          FIG. 10 is an isometric view of an alternative embodiment of the present  
20   invention;

          FIG. 11 is an exploded isometric view of a further alternative embodiment of the present invention;

          FIG. 12 is an isometric view of yet another alternative embodiment of the present invention.

25

## DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a cross sectional view of an IV tube enclosed within an infusion pump, at the load cell. The IV tube 100 is compressed between a clamping member 102 and a force sensor assembly 104. Ideally the IV tube 100 is positioned  
30   directly over the force sensor assembly 104, centered on centerline 106, such that the measured force at the force sensor assembly and a force created by the internal pressure of the IV tube 100 lie along the same plane. While this ideal condition

ensures high force measurement accuracy, it is often difficult to guarantee under normal operating conditions.

FIG. 2 shows an exploded isometric view of an embodiment of the present invention. The sensor assembly 200 comprises a housing structure 202 defining a hole therethrough 204. A pressure or load cell 206 is disposed within the housing 202. The load cell 206 is preferably located directly under the aforementioned hole 204 and is of any typical construction (i.e. gel or oil filled with micro-machined silicon die, direct die contact, strain gage etc.). The load cell is selected to have a particular construction that provides little or no mechanical friction in its force transfer mechanism (not shown) to its sensing element (not shown) and is also relatively insensitive to the location of the measured applied force. A suitable sensor may be similar to the sensor disclosed in U.S. Patent No. 5,760,313 which is hereby incorporated by reference. An actuation plunger 216 is fastened, by means of a screw 210 or the like, to a low mechanical friction hinge 208 that provides support in all directions, but allows rotation in an actuation direction. Such a hinge may, for example, be a living hinge or a small pin pivot hinge as depicted by reference numeral 1102 in FIG. 11. The living hinge may for example be a resilient metal or plastic strip, as is known in the art. Hinge 208 is in turn fastened to the housing 202 by means of another screw 212. It should be appreciated that one could use other fastening means instead of screws 210 and 212, such as for example glue or rivets. Both the shape of the plunger's upper surface 214 and the shape of the plunger's underside 218, may be varied to provide optimum results. This embodiment utilizes a circular shaped upper surface 214 and a chamfered underside 218. The underside 218 of the hinged plunger 216 is shaped so that it preferably contacts with the load cell 206 at a single contact point. Other shapes, such as for example a semicircular shaped underside, may also be utilized. A base 220 seals the housing 202 on the side distal from the hole 204. The base 220 furthermore fastens the sensor 206 in the housing 202 and includes contacts 222 disposed thereon, which connect outputs 224 from the sensor 206 to other measurement circuitry (not shown).

FIG. 3 shows an isometric view of the present invention with an IV tube in a first orientation. In this preferred embodiment, an IV drip tube 302 is placed across the sensor assembly 300, perpendicular to the hinge axis. This orientation is preferred

as the force sensor assembly 300 is not subject to a moment arm effect discussed *infra*. FIG. 4 illustrates a diagrammatic side view of the sensor assembly of FIG. 3. If the IV tubing crosses the plunger 402 off-center applying a force 400 to the plunger 402, the hinge, rotatable about hinge axis 404, provides a reaction force minimizing or preventing angulation of the plunger 402. This embodiment of the sensor assembly thus gives a more accurate reading irrespective of whether or not the tube is centered above the load cell 408 or not. Therefore, little or no reduction in force is transmitted to the load cell through the plunger from the IV tube if it is positioned off-center to the load cell.

FIG. 5 shows an isometric view of an embodiment of the invention. Sensor assembly 300 includes a modified upper surface 500 of the plunger. Square upper surface 500 is preferably utilized in conjunction with the embodiment described in relation to FIGS. 3 and 4, where the tube is oriented perpendicular to the hinge axis. The square shaped upper surface 500 maintains a constant area along the hinge axis.

FIG. 6 shows an isometric view of another embodiment of upper surface 600. The upper surface of the plunger may be shaped so that the tubing contact area changes with the distance of the IV tubing from the location of the center of the load cell. A change in the tubing contact area produces a change in the force transmitted to the plunger due to tubing internal pressure, and therefore a change in the force relationship with the load cell. Hourglass shaped upper surface 600 is also preferably utilized in conjunction with the embodiment described in relation to FIGS. 3 and 4. The hourglass shape, when implemented in the appropriate orientation to the hinge axis, can provide an increase in tubing contact area with an increase in the distance from the centerline of the load cell. This can counteract any loss in force to the load cell due to side loading of the hinge components, thus minimizing any effects of the IV tubing being off center.

FIG. 7 shows an isometric view of an alternative embodiment of the invention with an IV tube in a second orientation. In this embodiment, IV drip tube 700 is placed across the sensor assembly 702, parallel to the hinge axis.

FIG. 8 illustrates a diagrammatic side view of the sensor assembly shown in FIG. 7. A plunger 802 is pivotably hinged about a line 800, allowing the plunger to make single point contact with a load cell 804. When a force 806, caused by pressure

within the IV tube, is applied directly above the load cell 804, the load cell measures a reaction force 808 which is substantially the same as the applied force 806. However, as illustrated in FIG. 9, when a force 900 is applied off-center to the load cell 804, reaction force 902 measured at load cell 804 will be larger than the applied force 900, due to a moment arm effect. As there is no way to accurately determine the distance of the applied force 900 from hinge line 800, this orientation of the IV tube on the sensor assembly is not preferred. To overcome this problem, the shape of the upper surface of the plunger may once again be varied to compensate for the misalignment of the IV tube. Instead of a round upper surface of the plunger as shown in FIGS. 2, 3 and 7, or an hourglass shaped upper surface as shown in FIG. 6, the upper surface of the plunger may be shaped so that the tubing contact area changes with the distance of the IV tubing from the location the hinge axis 800. A change in the tubing contact area produces a change in transmitted force due to the tubing internal pressure and thus a change in the force relationship with the load cell. Variations in measured force caused by the misplacement of the tube on the upper surface of the plunger may therefore be counteracted by tailoring the shape of the upper surface of the plunger. As shown in FIG. 10, a triangular or tear drop shaped upper surface 1000, narrowing away from the hinge axis may preferably be utilized in conjunction with the embodiment described above in relation to FIGS. 7-9, where the tube is oriented parallel to the hinge axis.

FIG. 11 illustrates an exploded isometric view of another embodiment of the present invention. The living hinge 208 of FIG. 2 has been replaced with a plunger 1100 that is itself hinged to the housing 202 by means of a small hinge pin 1102. The separately hinged actuation plunger 1100 provides stability and low mechanical friction, resulting in low sensitivity to the positioning of an off-centered IV tube.

Other embodiments of the present invention may include a force assembly where the hinge and actuation plunger are formed integral with the hinge support housing (i.e. all molded together as one piece) instead of separate parts. FIG. 12 shows an embodiment of the present invention with a plastic living hinge 1200 integrated into the housing of the IV mechanism. The actuation plunger may also be held by flexible supports at several points around its circumference to minimize moment arm changes with tubing off-center positioning. Furthermore, the hinge could



WHAT IS CLAIMED IS:

1. A force sensor assembly for use in peristaltic pumps, comprising:  
a housing;  
5 a load cell at least partially disposed within said housing;  
a plunger, pivotable about an axis, where said plunger comprises:  
an upper surface; and  
an underside surface distal from said upper surface where said  
underside surface cooperates with said load cell; and  
10 a means for reducing said load cell's sensitivity to the positioning of an applied  
force on said upper surface.
2. A force sensor assembly according to claim 1, wherein said means for reducing  
said load cell's sensitivity, comprises an upper surface for receiving an intravenous  
15 tube perpendicular to said axis.
3. A force sensor assembly according to claim 2, wherein said upper surface is  
shaped to compensate for variations in measured force caused by the misalignment of  
said applied force.  
20
4. A force sensor assembly according to claim 3, wherein said upper surface  
shape is selected from a group consisting of the following shapes:  
circular, square or hourglass.
- 25 5. A force sensor assembly according to claim 1, wherein said means for reducing  
said load cell's sensitivity, comprises an upper surface for receiving an intravenous  
tube parallel to said axis.
6. A force sensor assembly according to claim 5, wherein said upper surface is  
30 shaped to compensate for variations in measured force caused by the misalignment of  
said applied force.

7. A force sensor assembly according to claim 6, wherein said upper surface shape is selected from a group consisting of the following shapes:  
circular, teardrop or triangular.

5 8. A force sensor assembly according to claim 1, wherein said plunger further comprises:

a free end; and  
a pivot end located at said axis.

10 9. A force sensor assembly according to claim 8, wherein said pivot end is rotatably coupled to said housing.

10. A force sensor assembly according to claim 8, wherein said pivot end is rotatably coupled to a body proximate said housing.

15

11. A force sensor assembly according to claim 8, wherein said pivot end is rotatably coupled to said housing by means of a hinge.

12. A force sensor assembly according to claim 11, wherein said is hinge is a  
20 living hinge.

13. A force sensor assembly according to claim 12, wherein said living hinge is a resilient metal strip.

25 14. A force sensor assembly according to claim 12, wherein said living hinge is a resilient plastic strip.

15. A force sensor assembly according to claim 11, wherein said hinge is a small pin pivot hinge.

30

16. A force sensor assembly according to claim 15, wherein said hinge has low mechanical friction.

17. A force sensor assembly according to claim 1, wherein said load cell is a pressure transducer.

5 18. A force sensor assembly according to claim 1, wherein said load cell has low internal mechanical friction.

19. A force sensor assembly according to claim 1, wherein said load cell itself has a reduced sensitivity to the positioning of the applied force on said upper surface..

10

20. A force sensor assembly according to claim 1, wherein said underside of said plunger is shaped to contact with said load cell at a single point.

21. A force sensor assembly according to claim 1, wherein said plunger is biased  
15 away from said load cell.

22. A force sensor assembly adapted to reduce a load cell's sensitivity to the positioning of an applied force, comprising:

a housing;

20 a load cell at least partially disposed within said housing; and

a plunger rotatably coupled to said housing by means of a hinge, said plunger further comprising:

an upper surface which is shaped to compensate for variations in measured force caused by the misalignment of said applied force.; and

25 an underside surface distal from said upper surface,

such that in use a force applied to said upper surface of said plunger is transferred to said load cell by said underside of said plunger pivoting into contact with said load cell.

30 23. A force sensor assembly according to claim 22, wherein said hinge is a living hinge.

24. A force sensor assembly according to claim 23, wherein said hinge is a small pin pivot hinge.

8236-0043-999

## ABSTRACT

A force sensor assembly for use in peristaltic pumps includes a housing and a load cell at least partially disposed within the housing. A plunger, pivotable about an axis, has an upper surface and an underside surface distal from the upper surface. The  
5 underside surface cooperates with the load cell. The force sensor further includes a mechanism to reduce the load cell's sensitivity to the positioning of an applied force on the upper surface.

8236-0043-999




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

# DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below at 201 et seq. underneath my name.

I believe I am the original, first and sole inventor if only one name is listed at 201 below, or an original, first and joint inventor if plural names are listed at 201 et seq. below, of the subject matter which is claimed and for which a patent is sought on the invention entitled

## Force Sensor Assembly for an Infusion Pump

and for which a patent application:

- ☒ is attached hereto and includes amendment(s) filed on (if applicable)  
☐ was filed in the United States on as Application No. (for declaration not accompanying application)  
 with amendment(s) filed on (if applicable)  
☐ was filed as PCT international Application No. on and was amended under PCT Article 19 on (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified application, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

EARLIEST FOREIGN APPLICATION(S), IF ANY, FILED PRIOR TO THE FILING DATE OF THE APPLICATION			
APPLICATION NUMBER	COUNTRY	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
			YES <input type="checkbox"/> NO <input type="checkbox"/>
			YES <input type="checkbox"/> NO <input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

APPLICATION NUMBER	FILING DATE

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NO.	FILING DATE	STATUS		
		PATENTED	PENDING	ABANDONED

POWER OF ATTORNEY: As a named inventor, I hereby appoint S. Leslie Misrock (Reg. No. 18872), Harry C. Jones, III (Reg. No. 20280), Berj A. Terzian (Reg. No. 20060), David Weild, III (Reg. No. 21094), Jonathan A. Marshall (Reg. No. 24614), Barry D. Rein (Reg. No. 22411), Stanton T. Lawrence, III (Reg. No. 25736), Charles E. McKenney (Reg. No. 22795), Philip T. Shannon (Reg. No. 24278), Francis E. Morris (Reg. No. 24615), Charles E. Miller (Reg. No. 24576), Gidon D. Stern (Reg. No. 27469), John J. Lauter, Jr. (Reg. No. 27814), Brian M. Poissant (Reg. No. 28462), Brian D. Coggio (Reg. No. 27624), Rory J. Radding (Reg. No. 28749), Stephen J. Harbulak (Reg. No. 29166), Donald J. Goodell (Reg. No. 19766), James N. Palik (Reg. No. 25510), Thomas E. Friebe (Reg. No. 29258), Laura A. Coruzzi (Reg. No. 30742), Jennifer Gordon (Reg. No. 30753), Allan A. Fanucci (Reg. No. 30256), Geraldine F. Baldwin (Reg. No. 31232), Victor N. Balancia (Reg. No. 31231), Samuel B. Abrams (Reg. No. 30605), Steven I. Wallach (Reg. No. 35402), Marcia H. Sundeen (Reg. No. 30893), Paul J. Zegger (Reg. No. 33821), Edmond R. Bannon (Reg. No. 32110), Bruce J. Barker (Reg. No. 33291), Adriane M. Antler (Reg. No. 32605), Thomas G. Rowan (Reg. No. 34419), James G. Markey (Reg. No. 31636), Thomas D. Kohler (Reg. No. 32797), Scott D. Stimpson (Reg. No. 33607), Gary S. Williams (Reg. No. 31066), William S. Galliani (Reg. No. 33885), Ann L. Gisolfi (Reg. No. 31956), Todd A. Wagner (Reg. No. 35399), Scott B. Familant (Reg. No. 35514), Kelly D. Talcott (Reg. No. 39582), Francis D. Cerrito (Reg. No. 38100), Anthony M. Insogna (Reg. No. 35203), Brian M. Rothery (Reg. No. 35340), Brian D. Siff (Reg. No. 35679), and Alan Tenenbaum (Reg. No. 34939), all of Pennie & Edmonds LLP, whose addresses are 1155 Avenue of the Americas, New York, New York 10036, 1667 K Street N.W., Washington, DC 20006 and 3300 Hillview Avenue, Palo Alto, CA 94304, and each of them, my attorneys, to prosecute this application, and to transact all business in the Patent and Trademark Office connected therewith.

SEND CORRESPONDENCE TO:		PENNIE & EDMONDS LLP 1155 Avenue of the Americas New York, N.Y. 10036-2711		DIRECT TELEPHONE CALLS TO: PENNIE & EDMONDS LLP DOCKETING (212) 790-2803	
2 0 1	FULL NAME OF INVENTOR	LAST NAME MORRIS	FIRST NAME MATTHEW	MIDDLE NAME GERALD	
	RESIDENCE & CITIZENSHIP	CITY San Diego	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP USA	
	POST OFFICE ADDRESS	STREET 3536 Lowell Street	CITY San Diego	STATE OR COUNTRY CA	ZIP CODE 92106
2 0 2	FULL NAME OF INVENTOR	LAST NAME SCHWARTZ	FIRST NAME DONALD	MIDDLE NAME FREDERIC	
	RESIDENCE & CITIZENSHIP	CITY San Diego	STATE OR FOREIGN COUNTRY California	COUNTRY OF CITIZENSHIP USA	
	POST OFFICE ADDRESS	STREET 7025 Charmant Drive, #301	CITY San Diego	STATE OR COUNTRY CA	ZIP CODE 92122

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon

SIGNATURE OF INVENTOR 201	<i>Math &amp; Morris</i>
DATE	<i>February 15, 2000</i>
SIGNATURE OF INVENTOR 202	<i>Donald Frederic Schwartz</i>
DATE	<i>February 15, 2000</i>